



| ELECTRICAL CHARACTERISTIC | |
|---------------------------|--|
| ① | CONTACT RESISTANCE: $\leq 20m\Omega$ MAX |
| ② | INSULATION RESISTANCE: $\geq 100M\Omega$ Min |
| ③ | WITHSTAND VOLTAGE: DC200V |
| ④ | CURRENT RATING: 1A/DC200V |
| ⑤ | OPERATING TEMPERATURE: $-30^{\circ}C \sim 60^{\circ}C$ |

| 5 | DIELECTRIC | TEF | White |
|------|-----------------------|----------|---------|
| 4 | PIN | BRASS | Nickel |
| 3 | PLASTIC RING | ABS | RD/WH |
| 2 | NUT | BRASS | Nickel |
| 1 | BODY | BRASS | Nickel |
| ITEM | DESIGNATION | MATERIAL | FINISH |
| REV | PART NO. & SAMPLE NO. | | DATE BY |
| A | JR 0877G | | |

| TOLERANCE | SIGNATURES | DATE |
|-----------------------------|---------------------------------|----------|
| 0 - 10 ± 0.05 | DRAFT: CHECKED: APPROVAL: | |
| 10 - 99 ± 0.5 | | |
| 100 - 999 ± 10.0 | | |
| 1000 - 9999 ± 100.00 | | |
| 10000 - 99999 ± 1000.00 | | |
| | SCALE | UNIT REV |
| SHEET | | |

| TITLE |
|--|
| RCA Chassis Mount Jack Nickel Plate (Red/White) |