

# FURUTECH

PURE TRANSMISSION

## Reference III Cables

---



Top of the line double-shielded  $\alpha$  (Alpha)-OCC conductor interconnects, power cords and digital cables featuring extraordinary build quality and Formula GC-303 antimagnetic EMI-absorbent modules surrounding the cable offering greater resolution, more powerful dynamics, and virtuoso performances from all your components. All connectors are rhodium-plated for optimal signal transfer.

---

### Features:

- Double-shielded  $\alpha$  (Alpha) $\mu$ -Conductors eliminate radiated noise
- Formula GC-303 Antimagnetic EMI-Absorbent Modules surround each cable
- High performance beautifully engineered rhodium-plated IEC [FI-25 (R)] and power connector [FI-25M (R)]
- Male: Rhodium-plated nonmagnetic pure copper
- Female: Rhodium-plated phosphor bronze
- Furutech's unique wire-clamping mechanism guarantees ultra firm connections for Furutech Pure Transmission signal
- Twin Flexible PVC sheaths improve vibration isolation.
- Insulated with high-quality polyethylene PE reducing capacitance
- Results in greater resolution, clarity, powerful dynamics, and an ultra-quiet soundstage in which music develops more fully without artificial upper-frequency "presence region" glare.
- GC-303 allows a deeper, tighter bass to form a solid foundation for the rest of the frequency range, better defining the original recording's venue. Natural, unforced detail reveals nuance and energy for an engaging musical experience.
- $\alpha$  (Alpha) Conductor Is Composed Of Fine PCOCC Wire Strands
- Treated With Furutech's  $\alpha$  (Alpha) Cryogenic and Demagnetizing Process





-- Srajan Ebaen, 6moons.com

## SPECIFICATIONS

---

### Construction and Materials

•49-strand  $\alpha$  (Alpha)  $\mu$ -conductor •0.32mm x 3 cores, 2.5mm diameter

---

•Insulation: Irradiated PE (Red/Natural/Yellow) 5mm diameter

•Sheath: Two layers flexible PVC (Dark Green) 15mm diameter

•Shield: Special EMI- and noise-absorbent Formula GC-303 module

### Here's What The Critics Say-

“The Furutech cable sound is easily described as one that completely avoids those peculiar striations that result from highlighting, the providence of certain silver cables that emphasize edge definition for nearly surreal image lock. Such sharp edging then becomes synonymous with etching. It gives a short-lived appearance of exceptional detail - short-lived since such sound is not only unrealistic but fatiguing.

“The Furutech cables patently don't cause this. However, they are exceptionally detailed. I can't help but think that the hexagonal barrel innards [Formula GC-303 Modules] are at least somewhat responsible for this wealth of clearly intelligible inner detail. Rather than throwing detail at you, they throw out inter-note noise. While the end result might seem the same -- more detail -- the way it communicates is very different. Put plainly, the Furutechs never fatigue even at elevated levels yet they do remain ultra resolved.”

•Jacket: Nylon yarn braid approx. 16.5mm diameter

•US Connectors: IEC [FI-25 (R)] and [FI-25M (R)]

•UK,/Europe/Australian Connectors: [FI-UK1363 (R)] • [FI-E35 (R)] • [FI-AU3112 (R)]

### Electrical Properties of Cable Test Method

•Max. Conductor Resistance 5.2  $\Omega$ /km JISC3005 6 20°C

•Min. Insulation Resistance 2500 M $\Omega$ -km JISC3005 9.1 20°C

•Dielectric Strength AC.3000 V/1 min. JISC3005